

## ANC-800V

### Wireless Auto Pan / Tilt MPEG4 Internet Camera

*Built-In Web Server/Zoom  
Auto Pan 270° / Tilt 135°*



ANC-800V (Wire)

ANC-800W (Wireless)



Connections

### Features

- Real Time Surveillance For:  
Home / Shop / Office / Cropper Planting / Bird Watching / Weather / Construction  
Parking Lot / Airport / Aircraft
- CCD Sensor for superior Quality Image
- High Quality MPEG4 Short Header Mode Compression
- ANC-800V / W enables you to view other rooms in your home, office or elsewhere while you are in the same building or in a different building.
- Motorized Pan 270° side to side, Tilt 135° up and down, 4X digital Zoom
- Easy to install and use
- You can manage anywhere, any time in the world.
- Built-In Microphone for Audio Monitoring
- Built-In Motion Detection & Email Notification
- Package: Camera , Remote control , Power Adapter , Camera stand, AV Cable,  
Installation Software, Quick Installation Guide Manual on CD ,  
16 channels Monitoring & Recording Software free bundled.

#### Remark:

Installation Minimum System Requirements:

Internet Explorer 5.x or above / CPU : Pentium III, 800 MHz or above / Memory Size : 128 MB or above

VGA card resolution : 800 x 600 or above

## Specification

|  |  |
|--|--|
| <b>Power Input</b>                         | External Power Supply , 12VDC 1.5A   |
| <b>Remote Management</b>                   | Configuration and system log can be accessed via WEB Browser and FTP application remotely  |
| <b>Networking Protocol</b>                 | TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS and DHCP   |
| <b>Networking Application</b>              | DDNS support with several popular DDNS servers<br>UPnP support , SMTP client , FTP client , FTP server , HTTP server   |
| <b>Connectivity</b>                        | Enhanced 802.11b , 10BaseT or 100BaseT Fast Ethernet   |
| <b>Video Algorithm Supported</b>           | H.263+ (MPEG4 Short Header Mode)<br>Three adjustable image sizes and quality intelligent motion detection windows with flexible bit rate   |
| <b>Features</b>                            | MPEG4 short header mode compression for streaming video<br>JPEG compression for still image  |
| <b>Audio</b>                               | 24Kbps<br>Built-In omni-directional microphone   |
| <b>Video Resolution</b>                    | Up to 30fps at 160x120 , Up to 30fps at 320x240 (NTSC)<br>Up to 25fps at 176x144 , Up to 25fps at 352x288 (PAL)<br>ANC-800V/G Up to 10 frames at 704*480 (NTSC) or 704*576 (PAL) |
| <b>General I/O</b>                         | 1 OPTO-isolated sensor input (max.12VDC 50mA)<br>1 relay output (max.24VDC 1A, 125VAC 0.5A)  |
| <b>Camera Specification</b>                | 1/4 inch color CCD sensor<br>AGC, AWB<br>Electronic shutter: 1/60 ~ 1/150000 sec.<br>Fixed focus glass lens, F2.0, 1 LUX   |
| <b>Pan and Tilt Direction Control</b>      | Auto pan and auto patrol mode with precipitant stops<br>Pan: Range 270 degrees / Tilt: Range 135 degrees<br>10/100 Mbps Fast Ethernet  |
| <b>Ports</b>                               | Audio/Video output<br>External microphone input<br>External I/O  |
| <b>Security</b>                            | Administrator and user group protected<br>ID / Password authentication   |
| <b>Viewing System Requirement Protocol</b> | ActiveX  |
| <b>Operating System</b>                    | Microsoft Windows XP, 2000 , Me or 98SE  |
| <b>Browser</b>                             | Internet Explorer 5.x or above   |
| <b>LED indicator</b>                       | 1) Power 2) Post, connection, heartbeat  |
| <b>Dimension</b>                           | 105mm(L) x 95mm(W) x 110mm(H)  |
| <b>Weight</b>                              | ANC-800V: NET. 350g , ANC-800W: NET. 400g  |

Products specifications and design subject to change without notice.✳